

SAM 022823

UNIMAG Art PFA-60

Gruppe Kühlmittelbehälter
Hersteller UNIMAG
Art PFA-60



Totalinhalt
Kapazität
Papierfilterbreite
Papierfilterlänge
Pumpenmotorleistung
Abmessungen:
Länge
Breite
Höhe

140 l
60 l/min
500 mm
90 m
25 W

1350 mm
720 mm
660 mm



PFA PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:

1. Surface Grinding Machine	5. Braid Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM

SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. l	L	A	B	C	H	PUMP (H-P)	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	800	800	400	400	720	600	1/8	PF1/2"	25W
PFA-40	40	120	1300	1000	600	400	720	600	1/8	PF1/2"	25W
PFA-60	60	140	1350	1150	800	400	720	600	1/8	PF1/2"	25W
PFA-80	80	160	1400	1200	800	400	720	600	1/4	PF3/4"	25W
PFA-120	120	210	1500	1300	800	400	920	740	1/2	PF3/4"	40W
PFA-160	160	260	1800	1600	800	400	920	740	1/2	PF3/4"	40W
PFA-240	240	440	1550	1750	1060	450	1320	740	1	PF1"	60W
PFA-300	300	540	1550	1950	1060	450	1320	740	1	PF1"	60W
PFA-500	500	980	3240	2950	1060	450	1320	740	1 1/2	PF1 1/2"	60W