

SAM 022822**UNIMAG Art PFA-60**

Gruppe
Hersteller
Art

Kühlmittelbehälter
 UNIMAG
 PFA-60



Totalinhalt
 Kapazität
 Papierfilterbreite
 Papierfilterlänge
 Pumpenmotorleistung
 Abmessungen:
 Länge
 Breite
 Höhe

140 l
 60 l/min
 500 mm
 90 m
 25 W

1350 mm
 720 mm
 660 mm



PFA-120

PFA PAPER FILTER

FEATURES:


1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 10µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:	
1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing Machine	

DIMENSION DIAGRAM



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. L	L	A	B	C	H	PUMP (HP)	OUTLET	MOTOR	FILTER PAPER	Feeder
PFA-30	30	120	1050	850	600	400	720	600	1/8	PF 1/2"	25W	
PFA-40	40	120	1300	1000	600	400	720	600	1/8	PF 1/2"	25W	W 1000MM
PFA-60	60	140	1350	1150	600	400	720	600	1/8	PF 1/2"	25W	L 900M
PFA-80	80	160	1500	1300	600	400	720	600	1/4	PF 3/4"	25W	
PFA-120	120	210	1500	1300	600	400	900	700	1/2	PF 3/4"	40W	W 1000MM
PFA-160	160	260	1600	1600	600	400	900	700	1/2	PF 3/4"	40W	L 900M
PFA-240	240	440	1550	1350	1000	450	1350	740	1	PF 1"	60W	W 1000MM
PFA-300	300	640	2150	1950	1000	450	1350	740	1	PF 1"	90W	
PFA-500	500	980	3240	2500	1000	450	1350	740	1.5	PF 1.5"	60W	L 900M