

SAM 022824**UNIMAG Art PFA-60**

Gruppe
Hersteller
Art

Kühlmittelbehälter
 UNIMAG
 PFA-60




Totalinhalt
 Kapazität
 Papierfilterbreite
 Papierfilterlänge
 Pumpenmotorleistung
 Abmessungen:
 Länge
 Breite
 Höhe

140 l
 60 l/min
 500 mm
 90 m
 25 W
 1350 mm
 720 mm
 660 mm

**PFA-120**

APPLICATION:

1. Surface Grinding Machine	5. Broad Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM**PFA
PAPER FILTER****FEATURES:**

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

**SPECIFICATION**

MODEL	CAPACITY L/MIN	TANK VOL L	L	A	B	C	H	PUMP (H-P) INLET	OUTLET	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	1050	800	400	400	720	600	1/8"	PF1/2"	25W	NO
PFA-40	40	120	1300	1000	600	400	720	600	1/8"	PF1/2"	25W	WHEEL
PFA-60	60	140	1350	1100	800	400	720	600	1/8"	PF1/2"	25W	WHEEL
PFA-80	80	160	1400	1100	800	400	720	600	1/4"	PF3/4"	25W	WHEEL
PFA-120	120	210	1500	1300	800	400	920	740	1/2"	PF3/4"	40W	WHEEL
PFA-160	160	260	1800	1600	800	400	920	740	1/2"	PF3/4"	40W	WHEEL
PFA-240	240	440	1550	1750	1000	400	1300	740	1"	PF1"	60W	WHEEL
PFA-300	300	540	2150	1950	1000	400	1300	740	1"	PF1"	60W	WHEEL
PFA-500	500	980	3240	2950	1000	400	1300	740	1 1/2"	PF1 1/2"	60W	WHEEL