


SAM 021969**FINETECH Art SMV 1370 H3L**

Gruppe	3-Achsen Bearbeitungszenter
Hersteller	FINETECH
Art	SMV 1370 H3L
Steuerung	FANUC Oi-MF Plus
Jahr	2022



Anzahl Achsen total	3
Tischlänge	1450 mm
Tischbreite	700 mm
Anzahl T-Nuten:	5
Abstand der T-Nuten	100 mm
T-Nutenbreite	18 mm
Max. Werkstückgewicht auf dem Tisch	1500 kg
Längsweg (X-Achse)	1300 mm
Querweg (Y-Achse)	700 mm
Vertikalweg (Z-Achse)	700 mm
Werkzeugmagazin Anzahl Werkzeugplätze	30
Werkzeugaufnahme: BT	40
Abstand zwischen Spindelnase und Tisch	130 - 830 mm
Spindeldrehzahl:	
Stufenlos	
von	0 t/min
bis	12000 t/min
Eilgang	25 m/min
Spindelmotor	18.5 kW
Gesamtleistungsbedarf	45 kVA
Maschinengewicht ca.	9000 kg
Abmessungen Maschine:	
Länge	4188 mm
Breite	2414 mm
Höhe	2560 mm

Diverses Zubehör:

Lineare Achsen Direktangetrieben	
Kühlmitteleinrichtung	
Kühlmitteleinrichtung	510 l
Kühlmittel durch die Spindel (IKZ)	20 bar
Ausblasvorrichtung für Spindelkonus	
Späneförderer	
Elektronisches Handrad	
Beleuchtung	
Spindelkühlung	
Spindelölkühler	
Spülpistole	
Blaspistole	
Automatisches Ausschalten	

www.mullermachines.ch

Zentralschmierung
Schaltschrank Klimagerät
Zustandsleuchte





MULLER MACHINES SA
top second hand and new precision machine tools

www.mullermachines.ch

Internationally Recognized Machine Tools From Finetech

From its beginnings in 1979, Finetech has been one of the top machine tool manufacturers in the world. Finetech manufactures a wide range of CNC vertical machining centers. Finetech's machines are built to deliver high speed with more accuracy, efficiency and durability with more standard features, high-tech innovations and solid engineering.


Every Finetech machine is designed to provide more flexibility and productivity, making for a very sound investment.



Finetech

Extensive Quality Control

Before shipping, each machining center from Finetech is subject to rigorous quality inspections during assembly. If it does not measure up to our standards, it does not leave our factory. Our objective is to ensure that each machine will provide optimum performance and fully satisfy customers.




SPINDLE THERMAL GROWTH TESTING
Each spindle is tested through the complete speed range and thermal growth is measured to ensure the spindle is within normal values.


SPINDLE DYNAMIC BALANCE TESTING
After machine assembly, the spindle is re-balanced to ensure smooth operation.



FINAL TEST CUT
Dynamic cutting process test ensures precision and performance of machine.



CALIBRATION
Every Finetech machine is laser calibrated for pitch error compensation and backlash.



BALL BAR TESTING
Every machine is put through a Dynamic Ballbar test to test circularity and reversal spike errors.

Extensive Quality Control During Assembly

Finetech



SPINDLE TRAM
Every spindle mount is hand scraped to ensure accurate alignment of the spindle to worktable.



BALLSCREW ALIGNMENT
The ballscrew bearing mounts are aligned using a precision test mandrel. The mounting surface is hand scraped to ensure a highly precise alignment.



GUIDEWAYS ARE FITTED WITH "TURCITE B"
Box way type machines are hand scraped and set matched to ensure high geometric accuracy.



STRAIGHTNESS
Every linear guideway has a precision ground mounting surface and is checked using a high precision Granite straight edge.



LEVEL
The machine level is continuously checked through each stage of the assembly process using precision levels.




SCREW AND LINEAR RAIL PARALLEL TEST
The straightness of the ballscrew is measured against the straightness of the linear guideway to ensure both components are parallel to each other.



THRUST BEARING ASSEMBLY
The thrust bearing housings are inspected and ground for proper clearances to allow the ballscrew to be properly supported.




SERVO MOTOR MOUNT
Each servo motor mounting surface is ground to ensure the motor is correctly aligned to the ballscrew.



EFFICIENT AXES LUBRICATION
Each axis uses volumetric oil or grease distribution to ensure even and efficient lubrication.



BALLSCREW MOUNT
The ball nut is hand scraped and aligned using a precision test mandrel.



Z AXIS ALIGNMENT TEST
The Z axis is tested for accuracy using a high precision granite square in X, Z and Y, Z directions.



MULLER MACHINES SA
top second hand and new precision machine tools

www.mullermachines.ch

Excellent Mechanical Features



Finetech




LINEAR WAY

CNC Vertical Machining Center

High Speed and Precision

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- All axes use an extra wide 45mm roller type linear guideway to allow the machining center to accommodate heavy loads with fast accelerations and low friction while maintaining accurate positioning.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-1270-H3L

LINEAR WAY SERIES





MULLER MACHINES SA
top second hand and new precision machine tools

www.mullermachines.ch

BOX WAY

Heavy Cutting Vertical Machining Center

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- All axes use box way design to allow the machining center to accommodate extremely heavy loads with smooth motion while increasing dampening of vibrations and cutting force characteristics.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-2590-3B

COMBINATION WAY


Combination Type Vertical Machining Center

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- The X and Y axes utilize roller type linear guideways to allow the machining center to accommodate heavy work piece loads with fast accelerations and low friction while maintaining accurate positioning.
- The Z axis uses box way design to allow the machining center to dampen heavier cutting forces.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-2090-2LB


BOX WAY SERIES



▲ 650-3B
• Travel : X650 Y500 Z500 mm
• Table : L800 x W470 mm



▲ 1060-3B
• Travel : X1000 Y600 Z650 mm
• Table : L1100 x W500 mm



▲ 1270-3B
• Travel : X1200 Y700 Z650 mm
• Table : L1300 x W700 mm



▲ 1570-3B
• Travel : X1500 Y700 Z650 mm
• Table : L1650 x W700 mm



▲ 1670-3B
• Travel : X1600 Y700 Z650 mm
• Table : L1750 x W700 mm



▲ 1890-3B
• Travel : X1800 Y1000 Z900 mm
• Table : L1950 x W900 mm



▲ 2090-3B
• Travel : X2000 Y1000 Z900 mm
• Table : L2150 x W900 mm




▲ 2290-3B
• Travel : X2200 Y1000 Z900 mm
• Table : L2350 x W1000 mm




▲ 2590-3B
• Travel : X2500 Y1000 Z900 mm
• Table : L2600 x W1000 mm

COMBINATION WAY SERIES



▲ 1060-2LB
• Travel : X1000 Y600 Z650 mm
• Table : L1100 x W600 mm



▲ 1270-2LB
• Travel : X1200 Y700 Z650 mm
• Table : L1350 x W700 mm



▲ 1570-2LB
• Travel : X1500 Y700 Z650 mm
• Table : L1650 x W700 mm



▲ 1670-2LB
• Travel : X1600 Y700 Z650 mm
• Table : L1750 x W700 mm



▲ 1890-2LB
• Travel : X1800 Y700 Z650 mm
• Table : L1950 x W900 mm



▲ 2070-2LB
• Travel : X2000 Y700 Z700 mm
• Table : L2150 x W700 mm



▲ 2090-2LB
• Travel : X2000 Y1000 Z1000 mm
• Table : L2150 x W1000 mm



▲ 2290-2LB
• Travel : X2200 Y1000 Z1000 mm
• Table : L2350 x W1000 mm



▲ 2590-2LB
• Travel : X2500 Y1000 Z1000 mm
• Table : L2600 x W1000 mm

www.mullermachines.ch

► Optional Equipment



Work Piece Measuring System	Tool Measuring System	CTS-Coolant Through Spindle
RENISHAW (OMP 40/60)	RENISHAW (TS27R)	20 BAR
BLUM (TC 50)	BLUM (Z3D)	50 BAR
HEIDENHAIN (TS 640)	HEIDENHAIN (TT 160)	60 BAR
	RENISHAW (NC-4)	70 BAR
	BLUM (NT)	120 BAR

 CTS-Coolant Through Spindle
 20/40/60/70 BAR
 Spindle Oil Cooler
 Oil Skimmer



 Transformer
 HEIDENHAIN Linear Scale
 HEIDENHAIN Rotary Encoder

 Gear Box
 4th Axis Rotary Table
 4/5th Axis Rotary Table

 Chain Type Chip Conveyor
 Screw Type Chip Auger

All Of Matching Checklist		
HEIDENHAIN Linear Scale	4/5th Axis Rotary Table	Screw Type Chip Auger
Built-in Coolant Nozzles	HEIDENHAIN Rotary Encoder	
Oil Skimmer	Gear Box	
Spindle Oil Cooler	Transformer	
4th Axis Rotary Table	Chain Type Chip Conveyor	