

SAM 022825**UNIMAG Art PFA-60**

Gruppe
Hersteller
Art

Kühlmittelbehälter
 UNIMAG
 PFA-60



Totalinhalt
 Kapazität
 Papierfilterbreite
 Papierfilterlänge
 Pumpenmotorleistung
 Abmessungen:
 Länge
 Breite
 Höhe

140 l
 60 l/min
 500 mm
 90 m
 25 W

1350 mm
 720 mm
 660 mm



PFA-120

PFA PAPER FILTER

FEATURES:



1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 80µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:	
1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing Machine	

DIMENSION DIAGRAM



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. L	L	A	B	C	H	PUMP (HP)	FILTER PAPER	WHEEL
PFA-30	30	120	1050	850	600	400	720	600	1/8 PP1/2"	25W
PFA-40	40	120	1300	1000	600	400	720	600	1/8 PP1/2"	W 1000MM
PFA-60	60	140	1350	1150	600	400	720	600	1/8 PP1/2"	W 1000MM
PFA-80	80	160	1500	1300	600	400	720	600	1/4 PP3/4"	25W
PFA-120	120	210	1500	1300	600	400	900	750	1/2 PP3/4"	40W
PFA-160	160	260	1600	1600	600	400	900	750	1/2 PP3/4"	40W
PFA-240	240	440	1550	1350	1000	450	1350	750	1 PP1"	60W
PFA-300	300	640	2150	1950	1000	450	1350	750	1 PP1"	90W
PFA-500	500	980	3240	2500	1000	450	1350	750	1 1/2 PP1 1/2"	60W