


SAM 022236**COLCHESTER Type COMBI 2000**

Group	CNC turning lathe, Cycle controlled lathe
Manufacturer	COLCHESTER
Type	COMBI 2000
Controller CNC	GE Fanuc Series 210i-T



Number of axis total	2
Centre height	200 mm
Distance between centres	1250 mm
Swing over cross-slide	246 mm
Swing over bed	400 mm
Spindle nose	D1-6
Spindle hole	54 mm
Cross slide:	
Travels:	
Longitudinal travel (Z-axis)	1156 mm
Transversal stroke (X axis)	240 mm
Rapid traverse X	10 m/min
Rapid traverse Z	20 m/min
Turret slide:	
Number of positions	8
Fixed tools turret	8
Type	DUPLOMATIC BSA 120
Spindle nose: VDI	30
Taper in spindle:	
Camlock	D1-6 CAMLOCK
Spindle speeds:	
from	12 t/min
up to	2500 t/min
Tailstock:	
Morse taper	5 CM
Spindle stroke	155 mm
Spindle diameter	73 mm
Spindle motor	7.5 kW
Voltage 50 Hz 3x	380 Volt
Various accessories:	
3-jaw chuck diameter	250 mm
Lamp	
Tailstock	
Coolant system	
Set of toolholders	



www.mullermachines.ch

