

SAM 022824**UNIMAG Type PFA-60**

Group Lubrification device
Manufacturer UNIMAG
Type PFA-60



Total Capacity
 Capacity
 Paper filter width
 Paper filter length
 Pump motor installed power
 Dimensions:
 Length
 Width
 Height


140 l
 60 l/min
 500 mm
 90 m
 25 W
 1350 mm
 720 mm
 660 mm



APPLICATION:

1. Surface Grinding Machine	5. Broad Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM




PFA PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:
 1. Standard accessory: one paper roll.
 2. Special specification is available.



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL L	L	A	B	C	H	PUMP (H-P) INLET	OUTLET	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	1050	800	400	400	720	600	1/8"	PF1/2"	25W	
PFA-40	40	120	1300	1000	600	400	720	600	1/8"	PF1/2"	25W	W1500MM
PFA-60	60	140	1350	1100	600	400	720	600	1/8"	PF1/2"	25W	L1500M
PFA-80	80	160	1400	1100	600	400	720	600	1/4"	PF3/4"	25W	
PFA-100	100	180	1500	1200	600	400	720	600	1/2"	PF3/4"	40W	W1700MM
PFA-120	120	200	1600	1300	600	400	720	600	1/2"	PF3/4"	40W	L1500M
PFA-140	140	220	1650	1350	600	400	720	600	1/2"	PF3/4"	40W	L1500M
PFA-160	160	240	1700	1400	600	400	720	600	1/2"	PF3/4"	40W	L1500M
PFA-240	240	440	2150	1750	1000	600	1320	740	1"	PF1"	60W	W1800MM
PFA-300	300	540	2150	1750	1000	600	1320	740	1"	PF1"	60W	W1800MM
PFA-500	500	980	3240	2550	1000	600	1330	740	1 1/2"	PF1 1/2"	60W	L1500M