


SAM 021969**FINETECH Type SMV 1370 H3L**

Group	3-axis machining center
Manufacturer	FINETECH
Type	SMV 1370 H3L
Controller CNC	FANUC 0i-MF Plus
Year	2022



Number of axis total	3
Table length	1450 mm
Table width	700 mm
Number of T-channels	5
Distance of the T-slots	100 mm
T-channel width	18 mm
Table load max.	1500 kg
Longitudinal travel (X-axis)	1300 mm
Transversal travel (y-axis)	700 mm
Vertical travel (z axis)	700 mm
Tool magazine number of tool places	30
Spindle nose: BT	40
Distance spindle nose to table	130 - 830 mm
Spindle speeds:	
stepless	
from	0 t/min
up to	12000 t/min
Rapid traverse:	25 m/min
Spindle motor	18.5 kW
Total power required	45 kVA
Machine's weight about	9000 kg
Overall dimensions machine:	
Length	4188 mm
Width	2414 mm
Height	2560 mm

Various accessories:

Linear Axes direct driven	
Coolant system	
Coolant system	510 l
Coolant through spindle (cts)	20 bar
Spindle blow out device	
Chip conveyor	
Handwheel electroinic	
Lamp	
Spindlecooling	
Spindle oil cooler	
Rinsing Guns	
Blow-off Guns	
Automatic switch off	

www.mullermachines.ch

Central lubrication
Switch cabinet Air conditioner
Status light





MULLER MACHINES SA
top second hand and new precision machine tools

www.mullermachines.ch

Internationally Recognized Machine Tools From Finetech

From its beginnings in 1979, Finetech has been one of the top machine tool manufacturers in the world. Finetech manufactures a wide range of CNC vertical machining centers. Finetech's machines are built to deliver high speed with more accuracy, efficiency and durability with more standard features, high-tech innovations and solid engineering.


Every Finetech machine is designed to provide more flexibility and productivity, making for a very sound investment.



Finetech

Extensive Quality Control

Before shipping, each machining center from Finetech is subject to rigorous quality inspections during assembly. If it does not measure up to our standards, it does not leave our factory. Our objective is to ensure that each machine will provide optimum performance and fully satisfy customers.




SPINDLE THERMAL GROWTH TESTING
Each spindle is tested through the complete speed range and thermal growth is measured to ensure the spindle is within normal values.


SPINDLE DYNAMIC BALANCE TESTING
After machine assembly, the spindle is re-balanced to ensure smooth operation.



FINAL TEST CUT
Dynamic cutting process test ensures precision and performance of machine.



CALIBRATION
Every Finetech machine is laser calibrated for pitch error compensation and backlash.



BALL BAR TESTING
Every machine is put through a Dynamic Ballbar test to test circularity and reversal spike errors.

Extensive Quality Control During Assembly


Finetech



SPINDLE TRAM
Every spindle mount is hand scraped to ensure accurate alignment of the spindle to worktable.



BALLSCREW ALIGNMENT
The ballscrew bearing mounts are aligned using a precision test mandrel. The mounting surface is hand scraped to ensure a highly precise alignment.



GUIDEWAYS ARE FITTED WITH "TURCITE B"
Box way type machines are hand scraped and set matched to ensure high geometric accuracy.



STRAIGHTNESS
Every linear guideway has a precision ground mounting surface and is checked using a high precision Granite straight edge.



LEVEL
The machine level is continuously checked through each stage of the assembly process using precision levels.




SCREW AND LINEAR RAIL PARALLEL TEST
The straightness of the ballscrew is measured against the straightness of the linear guideway to ensure both components are parallel to each other.




THRUST BEARING ASSEMBLY
The thrust bearing housings are inspected and ground for proper clearances to allow the ballscrew to be properly supported.



SERVO MOTOR MOUNT
Each servo motor mounting surface is ground to ensure the motor is correctly aligned to the ballscrew.



EFFICIENT AXES LUBRICATION
Each axis uses volumetric oil or grease distribution to ensure even and efficient lubrication.



BALLSCREW MOUNT
The ball nut is hand scraped and aligned using a precision test mandrel.



Z AXIS ALIGNMENT TEST
The Z axis is tested for accuracy using a high precision granite square in X, Z and Y, Z directions.



MULLER MACHINES SA
top second hand and new precision machine tools

www.mullermachines.ch

Finetech

Excellent Mechanical Features




LINEAR WAY

CNC Vertical Machining Center

High Speed and Precision

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- All axes use an extra wide 45mm roller type linear guideway to allow the machining center to accommodate heavy loads with fast accelerations and low friction while maintaining accurate positioning.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-1270-H3L

LINEAR WAY SERIES



Technical data and photographs without warranty.

Industriestrasse 22
CH-2555 Brugg BE / Switzerland

T +41 32 373 34 44

sales@mullermachines.ch
CHE-108.090.645 MWST



MULLER MACHINES SA
top second hand and new precision machine tools

www.mullermachines.ch

BOX WAY

Heavy Cutting Vertical Machining Center

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- All axes use box way design to allow the machining center to accommodate extremely heavy loads with smooth motion while increasing dampening of vibrations and cutting force characteristics.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-2590-3B

COMBINATION WAY

Combination Type Vertical Machining Center

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- The X and Y axes utilize roller type linear guideways to allow the machining center to accommodate heavy work piece loads with fast accelerations and low friction while maintaining accurate positioning.
- The Z axis uses box way design to allow the machining center to dampen heavier cutting forces.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.




▲ SMV-2090-2LB


BOX WAY SERIES



▲ 650-3B
• Travel : X650 Y500 Z500 mm
• Table : L800 x W470 mm



▲ 1060-3B
• Travel : X1000 Y600 Z650 mm
• Table : L1100 x W500 mm



▲ 1270-3B
• Travel : X1200 Y700 Z650 mm
• Table : L1300 x W700 mm



▲ 1570-3B
• Travel : X1500 Y700 Z650 mm
• Table : L1650 x W700 mm



▲ 1670-3B
• Travel : X1600 Y700 Z650 mm
• Table : L1750 x W700 mm



▲ 1890-3B
• Travel : X1800 Y1000 Z900 mm
• Table : L1950 x W900 mm



▲ 2090-3B
• Travel : X2000 Y1000 Z900 mm
• Table : L2150 x W900 mm



▲ 2290-3B
• Travel : X2200 Y1000 Z900 mm
• Table : L2350 x W1000 mm




▲ 2590-3B
• Travel : X2500 Y1000 Z900 mm
• Table : L2600 x W1000 mm

COMBINATION WAY SERIES



▲ 1060-2LB
• Travel : X1000 Y600 Z650 mm
• Table : L1100 x W600 mm



▲ 1270-2LB
• Travel : X1200 Y700 Z650 mm
• Table : L1350 x W700 mm



▲ 1570-2LB
• Travel : X1500 Y700 Z650 mm
• Table : L1650 x W700 mm



▲ 1670-2LB
• Travel : X1600 Y700 Z650 mm
• Table : L1750 x W700 mm



▲ 1890-2LB
• Travel : X1800 Y700 Z650 mm
• Table : L1950 x W900 mm



▲ 2070-2LB
• Travel : X2000 Y700 Z700 mm
• Table : L2150 x W700 mm



▲ 2090-2LB
• Travel : X2000 Y1000 Z1000 mm
• Table : L2150 x W1000 mm



▲ 2290-2LB
• Travel : X2200 Y1000 Z1000 mm
• Table : L2350 x W1000 mm



▲ 2590-2LB
• Travel : X2500 Y1000 Z1000 mm
• Table : L2600 x W1000 mm

► Optional Equipment



Work Piece Measuring System	Tool Measuring System	CTS-Coolant Through Spindle
RENISHAW (OMP 40/60)	RENISHAW (TS27R)	20 BAR
BLUM (TC 50)	BLUM (Z3D)	50 BAR
HEIDENHAIN (TS 640)	HEIDENHAIN (TT 160)	60 BAR
	RENISHAW (NC-4)	70 BAR
	BLUM (NT)	120 BAR

CTS-Coolant Through Spindle | 20/40/60/70 BAR | Spindle Oil Cooler | Oil Skimmer



Transformer | HEIDENHAIN Linear Scale | HEIDENHAIN Rotary Encoder

Gear Box | 4th Axis Rotary Table | 4/5th Axis Rotary Table

Chain Type Chip Conveyor | Screw Type Chip Auger

All Of Matching Checklist		
HEIDENHAIN Linear Scale	4/5th Axis Rotary Table	Screw Type Chip Auger
Built-in Coolant Nozzles	HEIDENHAIN Rotary Encoder	
Oil Skimmer	Gear Box	
Spindle Oil Cooler	Transformer	
4th Axis Rotary Table	Chain Type Chip Conveyor	