

SAM 022826

UNIMAG Type PFA-60

Group Lubrification device
Manufacturer UNIMAG
Type PFA-60



Total Capacity 140 l
Capacity 60 l/min
Paper filter width 500 mm
Paper filter length 90 m
Pump motor installed power 25 W
Dimensions:
Length 1350 mm
Width 720 mm
Height 660 mm



PFA
PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 10µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.



Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:

1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL L	PUMP (HP)							MOTOR	FILTER PAPER	WHEEL
			L	A	B	C	H	HP	OUTLET			
PFA-20	20	100	1050	850	600	400	720	600	1/8	PF 1/2"	25W	
PFA-40	40	120	1300	1050	600	400	720	600	1/8	PF 1/2"	25W	W 1000MM
PFA-60	60	140	1350	1150	600	400	720	600	1/8	PF 1/2"	25W	W 1000MM
PFA-80	80	160	1500	1300	600	400	720	600	1/4	PF 3/4"	25W	W 1000MM
PFA-120	120	210	1500	1300	600	400	900	700	1/2	PF 3/4"	40W	W 1000MM
PFA-160	160	260	1600	1600	600	400	900	700	1/2	PF 3/4"	40W	W 1000MM
PFA-240	240	440	1550	1350	1050	450	1350	740	1	PF 1"	60W	W 1000MM
PFA-300	300	640	2150	1950	1050	450	1350	740	1	PF 1"	90W	W 1000MM
PFA-500	500	980	3240	2950	1050	450	1350	740	1.5	PF 1.5"	60W	W 1000MM