

SAM 018293**TSCHUDIN Type HTG 610.10**

Group Cylindrical grinder
Manufacturer TSCHUDIN
Type HTG 610.10



Centre height	150 mm
Distance between centres	680 mm
Max. Longitudinal travel	620 mm
Grinding wheel:	
Diameter	350 mm
Bore	127 mm
grinding wheel width	50 mm
Grinding wheel speeds:	
number (steps)	3
from	1640 t/min
up to	2300 t/min
Work piece spindle head:	
speeds:	
stepless	
from	65 t/min
up to	500 t/min
rotatable	360 °
Spindle taper	5 CM
Taper in tailstock:	3 CM
Table angular displacement	8 °
Table speed:	
stepless	
up to	5 m/min
Voltage 50 Hz 3x	380 Volt
External Grinding wheel motor	4.0 CV
Total power required	7 CV
Machine's weight about	2'500 kg
Overall dimensions machine:	
Length	2700 mm
Width	1800 mm
Height	1900 mm
Various accessories:	
Digital readout number of axis:	2
Manufacturer	Tschudin Checkomatic
Paper filtration system	
Sparking-out attachment	
Lamp	
Raising block for centers	50 mm
Full automatic working cycle	
Infeed grinding	

www.mullermachines.ch

Intermittant grinding with left side infeed
Intermittant grinding with right side infeed
Intermittant grinding right and left side infeed
Preselected spark out time for all cycles



