

SAM 022819**UNIMAG Type PFA-40**

Group Lubrification device
Manufacturer UNIMAG
Type PFA-40




Total Capacity
 Capacity
 Paper filter width
 Paper filter length
 Pump motor installed power
 Dimensions:
 Length
 Width
 Height

120 l
 40 l/min
 500 mm
 90 m
 25 W
 1200 mm
 720 mm
 660 mm



APPLICATION:


1. Surface Grinding Machine	5. Broad Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM**PFA
PAPER FILTER****FEATURES:**

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

**SPECIFICATION**

MODEL	CAPACITY L/MIN	TANK VOL L	L	A	B	C	H	PUMP (H-P) INLET	OUTLET	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	1050	800	400	400	720	600	1/8"	PF1/2"	25W	
PFA-40	40	120	1300	1000	600	400	720	600	1/8"	PF1/2"	25W	W1500MM
PFA-60	60	140	1350	1100	600	400	720	600	1/8"	PF1/2"	25W	L150MM
PFA-80	80	160	1400	1100	600	400	720	600	1/4"	PF3/4"	25W	
PFA-120	120	210	1500	1300	800	400	920	740	1/2"	PF3/4"	40W	W1700MM
PFA-160	160	260	1800	1600	800	400	920	740	1/2"	PF3/4"	40W	L150MM
PFA-240	240	440	1550	1700	1000	400	1300	740	1"	PF1"	60W	
PFA-300	300	540	2150	1900	1000	400	1300	740	1"	PF1"	60W	W1800MM
PFA-500	500	980	3240	2900	1000	400	1300	740	1 1/2"	PF1 1/2"	60W	L150MM