

SAM 022817**UNIMAG Type PFA-40**

Group Lubrification device
Manufacturer UNIMAG
Type PFA-40



Total Capacity
 Capacity
 Paper filter width
 Paper filter length
 Pump motor installed power
 Dimensions:
 Length
 Width
 Height

120 l
 40 l/min
 500 mm
 90 m
 25 W


1200 mm
 720 mm
 660 mm



PFA-120

APPLICATION:	
1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM




PFA PAPER FILTER

FEATURES:

- Applicable to both ferrous and non-ferrous particles.
- Filter paper moves forward automatically when contaminants accumulate and clog it.
- Filtration effect depends on paper accuracy. Choose from 50μ, 10μ and 15μ.
- Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

- Standard accessory: one paper roll.
- Special specification is available.



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. L	L	A	B	C	H	PUMP (HP)	OUTLET	MOTOR	FILTER PAPER	Feeder
PFA-20	20	100	1050	850	600	400	720	600	1/8	PF 1/2"	25W	
PFA-40	40	120	1300	1050	600	400	720	600	1/8	PF 1/2"	25W	W 1000MM
PFA-60	60	140	1350	1150	600	400	720	600	1/8	PF 1/2"	25W	L 900M
PFA-80	80	160	1500	1300	600	400	720	600	1/4	PF 3/4"	25W	
PFA-120	120	210	1500	1300	600	400	900	750	1/2	PF 3/4"	40W	W 1000MM
PFA-160	160	260	1600	1600	600	400	900	750	1/2	PF 3/4"	40W	L 900M
PFA-240	240	440	1550	1350	1050	450	1350	750	1	PF 1"	60W	W 1000MM
PFA-300	300	640	2150	1950	1050	450	1350	750	1	PF 1"	90W	
PFA-500	500	980	3340	2500	1050	450	1350	750	1x2	PF 1 1/2"	60W	L 900M