

**SAM 021722****STEFOR Type RTA 500**

**Group** Surface grinder  
**Manufacturer** STEFOR  
**Type** RTA 500



|                              |            |
|------------------------------|------------|
| Table length                 | 660 mm     |
| Table width                  | 205 mm     |
| Grinding length              | 500 mm     |
| Grinding width               | 200 mm     |
| Execution:                   |            |
| hydraulic                    |            |
| Max. distance from table     |            |
| to spindle-centreline        | 425 mm     |
| Longitudinal travel (X-axis) | 550 mm     |
| Transversal travel (y axis)  | 200 mm     |
| Automatic cross-feed:        |            |
| stepless                     |            |
| from                         | 1 m/min    |
| up to                        | 30 m/min   |
| Table speeds:                |            |
| stepless                     |            |
| from                         | 1 m/min    |
| up to                        | 22 m/min   |
| Diameter of grinding wheel   | 225 mm     |
| Width of the grinding wheel  | 30 mm      |
| Grinding wheel speeds:       |            |
| number (steps)               |            |
| up to                        | 2800 t/min |
| Voltage 50 Hz 3x             | 380 Volt   |
| Grinding spindle motor       | 2.00 CV    |
| Total power required         | 3.00 CV    |
| Machine's weight about       | 850 kg     |
| Overall dimensions machine:  |            |
| Length                       | 1900 mm    |
| Width                        | 1200 mm    |
| Height                       | 1800 mm    |
| <b>Various accessories:</b>  |            |
| Magnetic plate:              |            |
| Length                       | 500 mm     |
| Width                        | 250 mm     |
| Redressing device            |            |
| Splash guard                 |            |



