

SAM 023299**NAKAMURA-TOME Type TW 10**

Group CNC turning lathe with two work spindles
Manufacturer NAKAMURA-TOME
Type TW 10



Number of spindles	2
Number of revolvers	2
Distance spindle nose	250 - 870 mm
Maximum turning length	160 mm
Max. turning diameter	130 mm
Turret carriage:	
Carriage 1:	
Longitudinal travel (Z-axis)	200 mm
Transversal stroke (X axis)	180 mm
Transversal travel (y-axis)	+/- 30 mm
Carriage 2:	
Longitudinal travel (Z-axis)	620 mm
Transversal stroke (X axis)	180 mm
Transversal travel (y-axis)	+/- 30 mm
Turret carriage:	
Turret slide: number	2
Number of positions turret 1	12
Number of positions turret 2	12
Driven tools turret 1	6
Driven tools turret 2	6
Spindle speeds	3600 t/min
Main spindle:	
Internal spindle diameter	42 mm
Spindle speeds:	
up to	5500 t/min
Spindle power	7.5 kW
Back spindle:	
Spindle hole	40 mm
max. speed	5000 t/min
Power of back spindle	5.5 kW
Voltage 50 Hz 3x	400 Volt
Various accessories:	
3-jaw chuck	
Set of collets	
Coolant system	
Bar feeder	LNS Hydrobar Mini-Sprint
Chip conveyor	
Set of toolholders	







