

SAM 022819

UNIMAG Type PFA-40

Group Lubrification device
Manufacturer UNIMAG
Type PFA-40



Total Capacity
Capacity
Paper filter width
Paper filter length
Pump motor installed power
Dimensions:
Length
Width
Height

120 l
40 l/min
500 mm
90 m
25 W

1200 mm
720 mm
660 mm



PFA
PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 80µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:

1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM

SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. (L)	L	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
PFA-20	20	100	1050	850	600	400	720	600	1/8	PF 1/2"	25W																		
PFA-40	40	120	1300	1050	600	400	720	600	1/8	PF 1/2"	25W																		
PFA-80	80	140	1350	1150	600	400	720	600	1/8	PF 1/2"	25W																		
PFA-120	120	160	1500	1300	600	400	720	600	1/8	PF 3/4"	25W																		
PFA-160	160	210	1500	1300	600	400	720	600	1/2	PF 3/4"	40W																		
PFA-240	240	260	1600	1600	600	400	720	600	1/2	PF 3/4"	40W																		
PFA-300	300	440	1550	1350	1050	450	1350	740	1	PF 1"	60W																		
PFA-360	360	640	2150	1950	1050	450	1350	740	1	PF 1"	90W																		
PFA-500	500	980	3340	2950	1050	450	1350	740	1x2	PF 1x2"	60W																		