

SAM 019561**DMG Type DMU 60 P hy-din**

Group	5-axis machining center
Manufacturer	DMG
Type	DMU 60 P hy-din
Controller CNC	HEIDENHAIN MillPlus /3R-WorkMaster + 3R-WorkShopManager
Year	2001



Number of axis simultaneous	5
Number of tables	1
Number of spindles	1
Circular table diameter	630 mm
Number of T-channels	9
Distance of the T-slots	63 mm
T-channel width	14H7 mm
Centering bore diameter	50H6 mm
Longitudinal travel (X-axis)	600 mm
Transversal travel (y-axis)	700 mm
Vertical travel (z axis)	600 mm
Dimension of the workpiece:	
Height	1000 mm
Diameter	920 mm
Table load max.	500 kg
Table divisions (B)	360 °
A axis	
Swivel angle (a-axis)	+45/-30 °
Holding torque A-axis	3866 Nm
Clamping torque C-axis	6'008 Nm
Torque max.	2650 Nm
Tool changer:	
Number of tools	180
Tool diameter	80 mm
Diameter with free adjacent pockets	160 mm
Tool lenght	350 mm
Max. tool-weight	10 kg
Spindle nose	SK
Spindle speeds:	40 DIN 69871
stepless	
up to	18000 t/min
Feeds:	
stepless	
longitudinal from	20 mm/min
up to	15000 mm/min
transversal from	20 mm/min
up to	15000 mm/min
vertical from	20 mm/min
up to	15000 mm/min
Rapid traverse:	40 m/min



www.mullermachines.ch

Measurement system:

Resolution

µm

Air connect

5 - 8 bar

Voltage 50 Hz 3x

400 Volt

Total power required

44 kVA

Noise level

80 dB (A)

Machine's weight about

7500 kg

Overall dimensions machine:

Length

7500 mm

Width

4500 mm

Height

2628 mm

Various accessories:

Set of toolholders

SK 40 ca 150x

High pressure coolant device

40 bar

Coolant through spindle (cts)

Tool setter Renishaw

Lamp

Rotating viewing window

Switch cabinet Air conditioner







