

**SAM 022817**

**UNIMAG Type PFA-40**

**Groupe** Bac de lubrification  
**Fabricant** UNIMAG  
**Type** PFA-40



Contenance totale 120 l  
Capacité 40 l/min  
Largeur de filtre de papier 500 mm  
Longueur de filtre de papier 90 m  
Puissance du moteur de la pompe 25 W  
Encombresments:  
Longueur 1200 mm  
Largeur 720 mm  
Hauteur 660 mm



**PFA PAPER FILTER**

**FEATURES:**

- Applicable to both ferrous and non-ferrous particles.
- Filter paper moves forward automatically when contaminants accumulate and clog it.
- Filtration effect depends on paper accuracy. Choose from 50µ, 80µ and 15µ.
- Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

**Remark:**

- Standard accessory: one paper roll.
- Special specification is available.

**APPLICATION:**

1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding machine	7. Planer
4. Honing machine	

**DIMENSION DIAGRAM**

**SPECIFICATION**

MODEL	CAPACITY L/MIN	TANK VOL. (L)	L	A	B	C	H	PUMP (HP)	FILTER PAPER	WHEEL	
PFA-20	20	100	1050	850	800	400	720	600	1/8	PP1/2"	25W
PFA-40	40	120	1300	1050	800	400	720	600	1/8	PP1/2"	25W W: 100MM
PFA-60	60	140	1350	1150	800	400	720	600	1/8	PP1/2"	25W L: 90M
PFA-80	80	160	1500	1300	800	400	720	600	1/8	PP3/4"	25W W: 100MM
PFA-120	120	210	1900	1500	800	400	920	750	1/2	PP3/4"	40W L: 90M
PFA-160	160	260	1900	1600	800	400	920	750	1/2	PP3/4"	40W W: 100MM
PFA-240	240	440	1550	1350	1060	450	1330	740	1	PP1"	60W W: 1000MM
PFA-300	300	640	2150	1950	1060	450	1330	740	1	PP1"	60W W: 1000MM
PFA-500	500	960	3340	2950	1060	450	1330	740	1.5	PP1.5"	60W W: 100M