

SAM 022826

UNIMAG Type PFA-60

Groupe Bac de lubrification
Fabricant UNIMAG
Type PFA-60



Contenance totale 140 l
Capacité 60 l/min
Largeur de filtre de papier 500 mm
Longueur de filtre de papier 90 m
Puissance du moteur de la pompe 25 W
Encombresments:
Longueur 1350 mm
Largeur 720 mm
Hauteur 660 mm



PFA PAPER FILTER

FEATURES:

- Applicable to both ferrous and non-ferrous particles.
- Filter paper moves forward automatically when contaminants accumulate and clog it.
- Filtration effect depends on paper accuracy. Choose from 50µ, 80µ and 15µ.
- Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

- Standard accessory: one paper roll.
- Special specification is available.

APPLICATION:

1. Surface Grinding Machine	5. Small Grinding Machine
2. Center Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding machine	7. Planer
4. Honing machine	

DIMENSION DIAGRAM

SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. (L)	L	A	B	C	H	H	PUMP (HP)	OUTLET	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	1050	850	800	400	720	600	1/8	PP1/2"	25W		
PFA-40	40	120	1300	1050	800	400	720	600	1/8	PP1/2"	25W	Ø 100MM	
PFA-60	60	140	1350	1150	800	400	720	600	1/8	PP1/2"	25W	Ø 100MM	WHEEL
PFA-80	80	160	1500	1300	800	400	720	600	1/8	PP3/4"	25W	Ø 100MM	WHEEL
PFA-120	120	210	1900	1500	800	400	920	740	1/2	PP3/4"	40W	Ø 100MM	WHEEL
PFA-160	160	260	1900	1600	800	400	920	740	1/2	PP3/4"	40W	Ø 100MM	WHEEL
PFA-240	240	440	1550	1350	1060	450	1330	740	1	PP1"	60W	Ø 100MM	NO
PFA-300	300	640	2150	1950	1060	450	1330	740	1	PP1"	60W	Ø 100MM	WHEEL
PFA-500	500	960	3340	2950	1060	450	1330	740	1.5	Ø 1.5"	60W	Ø 100MM	WHEEL