


SAM 021969**FINETECH Type SMV 1370 H3L**

Groupe	Centre d'usinage 3 axes
Fabricant	FINETECH
Type	SMV 1370 H3L
Commande	FANUC Oi-MF Plus
Année	2022



Nombre d'axes total	3
Longueur de la table	1450 mm
Largeur de la table	700 mm
Nombre rainures en T	5
Distance entre les rainures en T	100 mm
Largeur rainures en T	18 mm
Charge admise sur la table max.	1500 kg
Course longitudinale (axe-X)	1300 mm
Course transversale (Y)	700 mm
Course verticale (axe-Z)	700 mm
Magasin nombre de places d'outils	30
Cône de la broche: BT	40
Distance nez de broche et table	130 - 830 mm
Vitesse de la broche:	
Variateur (réglage progressif)	
de	0 t/min
à	12000 t/min
Avances rapide:	25 m/min
Moteur de la broche	18.5 kW
Puissance totale installée	45 kVA
Poids de la machine env.	9000 kg
Encombrement machine:	
Longueur	4188 mm
Largeur	2414 mm
Hauteur	2560 mm

Accessoires divers:

Axes linéaires entraînements directs	
Dispositif d'arrosage	
Dispositif d'arrosage	510 l
Arrosage par le centre de la broche	20 bar
Soufflage du cône	
Evacuateur de copeaux	
Manivelle électronique	
Lampe	
Refroidissement de la broche	
Refroidisseur d'huile de broche	
Pistolet de rincage	
Soufflets air comprimé	
Extinction automatique	

www.mullermachines.ch

Graissage central
Climatiseur armoire de commande
Lampe de statut



Internationally Recognized Machine Tools From Finetech

From its beginnings in 1979, Finetech has been one of the top machine tool manufacturers in the world. Finetech manufactures a wide range of CNC vertical machining centers. Finetech's machines are built to deliver high speed with more accuracy, efficiency and durability with more standard features, high-tech innovations and solid engineering.

Every Finetech machine is designed to provide more flexibility and productivity, making for a very sound investment.



Extensive Quality Control


Before shipping, each machining center from Finetech is subject to rigorous quality inspections during assembly. If it does not measure up to our standards, it does not leave our factory. Our objective is to ensure that each machine will provide optimum performance and fully satisfy customers.



SPINDLE THERMAL GROWTH TESTING
Each spindle is tested through the complete speed range and thermal growth is measured to ensure the spindle is within normal values.

FINAL TEST CUT
Dynamic cutting process test ensures precision and performance of machine.

SPINDLE DYNAMIC BALANCE TESTING
After machine assembly, the spindle is re-balanced to ensure smooth operation.



CALIBRATION
Every Finetech machine is laser calibrated for pitch error compensation and backlash.

BALL BAR TESTING
Every machine is put through a Dynamic Ballbar test to test circularity and reversal spike errors.


Extensive Quality Control During Assembly



SPINDLE TRAM
Every spindle mount is hand scraped to ensure accurate alignment of the spindle to worktable.



BALLSCREW ALIGNMENT
The ballscrew bearing mounts are aligned using a precision test mandrel. The mounting surface is hand scraped to ensure a highly precise alignment.



GUIDEWAYS ARE FITTED WITH "TURCITE B"
Box way type machines are hand scraped and set matched to ensure high geometric accuracy.



STRAIGHTNESS
Every linear guideway has a precision ground mounting surface and is checked using a high precision Granite straight edge.



LEVEL
The machine level is continuously checked through each stage of the assembly process using precision levels.




SCREW AND LINEAR RAIL PARALLEL TEST
The straightness of the ballscrew is measured against the straightness of the linear guideway to ensure both components are parallel to each other.



THRUST BEARING ASSEMBLY
The thrust bearing housings are inspected and ground for proper clearances to allow the ballscrew to be properly supported.



SERVO MOTOR MOUNT
Each servo motor mounting surface is ground to ensure the motor is correctly aligned to the ballscrew.



EFFICIENT AXES LUBRICATION
Each axis uses volumetric oil or grease distribution to ensure even and efficient lubrication.



BALLSCREW MOUNT
The ball nut is hand scraped and aligned using a precision test mandrel.



Z AXIS ALIGNMENT TEST
The Z axis is tested for accuracy using a high precision granite square in X, Z and Y, Z directions.

Excellent Mechanical Features



COOLANT-THROUGH-SPINDLE (CTS) 20-70 BAR (Optional)
Coolant-Through-Spindle provides coolant directly to the machining process through the center of the spindle. CTS may extend the life of the cutting tool and improve the evacuation of chips, especially when used for deep hole drilling and pocket milling.



SPINDLE CHILLER (Oil or Water)
The spindle chiller will help maintain a stable spindle temperature and will reduce the effects of thermal expansion of the spindle main shaft as well as extend the life of the spindle.



IN HOUSE CIRCUIT DESIGN
The Finetech R&D team can design both hardware and software components for the machine tools and allows for better quality control and quick response to customers requests.



Ø63mm EXTRA LARGE BALLSCREW
Finetech's model 1890 and larger use ø63mm ball screws to handle heavier cutting and table loads while still providing smooth motion.



AIR COUNTER BALANCE



LINEAR SCALE MOUNTING SURFACE
A precision ground surface can be added to each axis to allow for easy installation of linear scales by ensuring a straight and parallel surface.



T-SLOT GRINDING
Each T-Slot is ground to a H8 tolerance to provide an accurate datum surface allowing for easy and precise machine setup.

LINEAR WAY

CNC Vertical Machining Center

High Speed and Precision

- The casting assembly of the SMV machining centers has been designed using a Finite Element Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- All axes use an extra wide 45mm roller type linear guideway to allow the machining center to accommodate heavy loads with fast accelerations and low friction while maintaining accurate positioning.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



LINEAR WAY SERIES



<p>▲ 610-H3L</p> <ul style="list-style-type: none"> • Travel : 810 X400 Z460 mm • Table : L650 x W400 mm 	<p>▲ 710-H3L</p> <ul style="list-style-type: none"> • Travel : 1070 X450 Z460 mm • Table : L760 x W420 (500) mm 	<p>▲ 800-H3L</p> <ul style="list-style-type: none"> • Travel : 1360 X500 Z500 mm • Table : L950 x W500 mm
<p>▲ 850-H3L</p> <ul style="list-style-type: none"> • Travel : 1350 X600 Z550 mm • Table : L1000 x W500 mm 	<p>▲ 1060-H3L</p> <ul style="list-style-type: none"> • Travel : 1830 X600 Z650 mm • Table : L1100 x W600 mm 	<p>▲ 1270-H3L</p> <ul style="list-style-type: none"> • Travel : 1820 X700 Z700 mm • Table : L1350 x W700 mm
<p>▲ 1370-H3L</p> <ul style="list-style-type: none"> • Travel : 1830 X700 Z700 mm • Table : L1450 x W700 mm 	<p>▲ 1570-H3L</p> <ul style="list-style-type: none"> • Travel : 1850 X700 Z700 mm • Table : L1650 x W700 mm 	<p>▲ 1670-H3L</p> <ul style="list-style-type: none"> • Travel : 1850 X700 Z700 mm • Table : L1750 x W700 mm
<p>▲ 1685-H3L</p> <ul style="list-style-type: none"> • Travel : 1860 X850 Z850 mm • Table : L1600 x W800 mm 	<p>▲ 2070-H3L</p> <ul style="list-style-type: none"> • Travel : 2000 X700 Z700 mm • Table : L2150 x W700 mm 	

BOX WAY

Heavy Cutting Vertical Machining Center

- The casting assembly of the SMV machining centers has been designed using a Finite-Element-Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- All axes use box way design to allow the machining center to accommodate extremely heavy loads with smooth motion while increasing dampening of vibrations and cutting force characteristics.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-2590-3B

BOX WAY SERIES

 <p>▲ 650-3B • Travel : X650 Y500 Z500 mm • Table : L800 x W470 mm</p>	 <p>▲ 1060-3B • Travel : X1000 Y600 Z650 mm • Table : L1100 x W500 mm</p>	 <p>▲ 1270-3B • Travel : X1200 Y700 Z650 mm • Table : L1300 x W700 mm</p>
 <p>▲ 1570-3B • Travel : X1500 Y700 Z650 mm • Table : L1650 x W700 mm</p>	 <p>▲ 1670-3B • Travel : X1600 Y700 Z650 mm • Table : L1750 x W700 mm</p>	 <p>▲ 1890-3B • Travel : X1800 Y1000 Z900 mm • Table : L1950 x W900 mm</p>
 <p>▲ 2090-3B • Travel : X2000 Y1000 Z900 mm • Table : L2150 x W900 mm</p>	 <p>▲ 2290-3B • Travel : X2200 Y1000 Z900 mm • Table : L2350 x W1000 mm</p>	 <p>▲ 2590-3B • Travel : X2500 Y1000 Z900 mm • Table : L2600 x W1000 mm</p>

COMBINATION WAY

Combination Type Vertical Machining Center

- The casting assembly of the SMV machining centers has been designed using a Finite-Element-Analysis process to ensure the machine will handle cutting forces and weight loads associated with the demands of the machine specifications.
- The X and Y axes utilize roller type linear guideways to allow the machining center to accommodate heavy work piece loads with fast accelerations and low friction while maintaining accurate positioning.
- The Z axis uses box way design to allow the machining center to dampen heavier cutting forces.
- The machine base and saddle base utilize a wide design to prevent sagging and overhanging concerns with heavy work piece loads.
- The Z axis casting uses a reinforced rib design to achieve structural strength through the entire casting length.
- Each axis motor is directly coupled to the ball screw.
- Each axis will use a grade C3 precision ground ball screw and will use a pre-tensioned design to improve machine performance.



▲ SMV-2090-2LB

COMBINATION WAY SERIES

 <p>▲ 1060-2LB • Travel : X1000 Y600 Z650 mm • Table : L1100 x W600 mm</p>	 <p>▲ 1270-2LB • Travel : X1200 Y700 Z650 mm • Table : L1350 x W700 mm</p>	 <p>▲ 1570-2LB • Travel : X1500 Y700 Z650 mm • Table : L1650 x W700 mm</p>
 <p>▲ 1670-2LB • Travel : X1600 Y700 Z650 mm • Table : L1750 x W700 mm</p>	 <p>▲ 1890-2LB • Travel : X1800 Y900 Z900 mm • Table : L1950 x W900 mm</p>	 <p>▲ 2070-2LB • Travel : X2000 Y700 Z700 mm • Table : L2150 x W700 mm</p>
 <p>▲ 2090-2LB • Travel : X2000 Y1000 Z1000 mm • Table : L2150 x W1000 mm</p>	 <p>▲ 2290-2LB • Travel : X2200 Y1000 Z1000 mm • Table : L2350 x W1000 mm</p>	 <p>▲ 2590-2LB • Travel : X2500 Y1000 Z1000 mm • Table : L2600 x W1000 mm</p>

► Optional Equipment



Work Piece Measuring System	Tool Measuring System	CTS-Coolant Through Spindle
RENISHAW (OMP 40/60)	RENISHAW (TS27R)	20 BAR
BLUM (TC 50)	BLUM (Z3D)	50 BAR
HEIDENHAIN (TS 640)	HEIDENHAIN (TT 160)	60 BAR
	RENISHAW (NC-4)	70 BAR
	BLUM (NT)	120 BAR



All Of Matching Checklist		
HEIDENHAIN Linear Scale	4/5th Axis Rotary Table	Screw Type Chip Auger
Built-in Coolant Nozzles	HEIDENHAIN Rotary Encoder	
Oil Skimmer	Gear Box	
Spindle Oil Cooler	Transformer	
4th Axis Rotary Table	Chain Type Chip Conveyor	