

SAM 022825**UNIMAG Type PFA-60**

Groupe
Fabricant
Type

Bac de lubrification
 UNIMAG
 PFA-60



Contenance totale
 Capacité
 Largeur de filtre de papier
 Longueur de filtre de papier
 Puissance du moteur de la pompe
 Encombresments:

Longueur
 Largeur
 Hauteur

140 l
 60 l/min
 500 mm
 90 m
 25 W

1350 mm
 720 mm
 660 mm



PFA-120

APPLICATION:

1. Surface Grinding Machine	5. Broad Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing machine	

PFA PAPER FILTER


FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

DIMENSION DIAGRAM



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL L	L	A	B	C	H	PUMP (H-P) INLET	OUTLET	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	1050	800	400	400	720	600	1/8"	PF1/2"	25W	
PFA-40	40	120	1300	1000	600	400	720	600	1/8"	PF1/2"	25W	W1500MM
PFA-60	60	140	1350	1100	600	400	720	600	1/8"	PF1/2"	25W	L1500M
PFA-80	80	160	1400	1100	600	400	720	600	1/4"	PF3/4"	25W	
PFA-100	100	180	1500	1100	600	400	720	600	1/2"	PF3/4"	40W	W1700MM
PFA-120	120	210	1500	1300	800	400	920	740	1/2"	PF3/4"	40W	L1500M
PFA-140	140	260	1800	1600	800	400	920	740	1/2"	PF3/4"	40W	L1500M
PFA-240	240	440	1550	1700	1000	400	1300	740	1"	PF1"	60W	
PFA-300	300	540	2150	1900	1000	400	1300	740	1"	PF1"	60W	W11000MM
PFA-500	500	980	3240	2900	1000	400	1300	740	1 1/2"	PF1 1/2"	60W	L1500M