

SAM 020883**TSCHUDIN Tipo HTG 622**

Gruppo Rettificatrice per cilindri
Produttori TSCHUDIN
Tipo HTG 622



Altezza punte	100 mm
Distanza fra le punte	680 mm
Course longitudinale maxi	620 mm
Corsa trasversale maxi.	45 mm
Mola:	
Diametro	500 mm
Larghezza	80 mm
Alesaggio	203 mm
larghezza massimo della mola	80 mm
Giri della mola:	
numeri (gradini)	3
da	1150 t/min
fino	1550 t/min
Testa porta mola girevole	3 °
Testa porta pezzo:	
giri:	
con variatore continuo	
da	65 t/min
fino	500 t/min
girevole	360 °
Attacco mandrino	4 CM
Cono della contropunta:	3 CM
Corsa canotto	20 mm
Forza pressione	4 - 15 kp
Inclinazione massimo tavola	9 °
Velocità della tavola:	
con variatore continuo	
fino	5 m/min
Collegamento 50 Hz 3x	380 Volt
Motore mandrino portamola ext.	5.5 kW
Motore testa porta-pezzo	0.7 CV
Potenza totale installata	10 CV
Peso della macchina circa	2'900 kg
Dimensioni macchina:	
Lunghezza	2300 mm
Larghezza	1800 mm
Altezza	1900 mm

Accessori diversi:

Ravvivatore

www.mullermachines.ch

Refrigerazione
Filtro a carta
Contropunta



A close-up photograph of a mechanical assembly mounted on a lathe machine. The assembly consists of a green base block, a silver-colored metal block with a central hole, and a yellow conical component. A blue cable is connected to a green sensor or actuator on the machine's frame. The background shows the industrial setting of a workshop.



Dati tecnici e fotografie senza garanzia.
Industriestrasse 22
CH-2555 Brugg BE / Switzerland

sales@mullermachines.ch
CHE-108.090.645 MWST