

SAM 022815**UNIMAG Tipo PFA-20****Gruppo**

Lubrificazione

Produttori

UNIMAG

Tipo

PFA-20



Contenuto massima
 Capacità
 Larghezza del filtro in carta
 Lunghezza filtro di carta
 Motore pompa
 Dimensioni:
 Lunghezza
 Larghezza
 Altezza

100 l
 20 l/min
 500 mm
 90 m
 25 W

1050 mm
 720 mm
 660 mm



PFA-120

PFA PAPER FILTER

FEATURES:


1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 80µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:	
1. Surface Grinding Machine	5. Bore Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing Machine	

DIMENSION DIAGRAM



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. L	L	A	B	C	H	PUMP (HP)	FILTER PAPER	WHEEL
PFA-20	20	100	1050	850	600	400	720	600	1/8 PP1/2"	25W
PFA-40	40	120	1300	1050	600	400	720	600	1/8 PP1/2"	25W
PFA-60	60	140	1350	1150	600	400	720	600	1/8 PP1/2"	25W
PFA-80	80	160	1500	1300	600	400	720	600	1/4 PP3/4"	25W
PFA-120	120	210	1500	1300	600	400	720	750	1/2 PP3/4"	40W
PFA-160	160	260	1600	1600	600	400	820	750	1/2 PP3/4"	40W
PFA-240	240	440	1550	1350	1050	450	1350	750	1 PP1"	60W
PFA-300	300	640	2150	1950	1050	450	1350	750	1 PP1"	90W
PFA-500	500	980	3240	2500	1050	450	1350	750	1 1/2 PP1 1/2"	60W