

SAM 022825**UNIMAG Tipo PFA-60****Gruppo**

Lubrificazione

Produttori

UNIMAG

Tipo

PFA-60



Contenuto massima
 Capacità
 Larghezza del filtro in carta
 Lunghezza filtro di carta
 Motore pompa
 Dimensioni:

Lunghezza
 Larghezza
 Altezza

140 l
 60 l/min
 500 mm
 90 m
 25 W

1350 mm
 720 mm
 660 mm



**PFA
PAPER FILTER**

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:

1. Surface Grinding Machine	5. Broad Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing Machine	

DIMENSION DIAGRAM

SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL L	L	A	B	C	H	PUMP (H-P) HP	OUTLET	MOTOR	FILTER PAPER	WHEEL
PFA-20	20	100	1050	800	400	400	720	600	1/8	PF1/2"	25W	
PFA-40	40	120	1300	1000	600	400	720	600	1/8	PF1/2"	25W	WHEEL
PFA-60	60	140	1350	1100	600	400	720	600	1/8	PF1/2"	25W	WHEEL
PFA-80	80	160	1400	1100	600	400	720	600	1/4	PF3/4"	25W	WHEEL
PFA-120	120	210	1500	1300	800	400	920	740	1/2	PF3/4"	40W	WHEEL
PFA-160	160	260	1800	1600	800	400	920	740	1/2	PF3/4"	40W	WHEEL
PFA-240	240	440	1550	1700	1000	400	1300	740	1	PF1"	60W	WHEEL
PFA-300	300	540	2150	1900	1000	400	1300	740	1	PF1"	60W	WHEEL
PFA-500	500	980	3240	2900	1000	400	1300	740	1K2	PF1"x2"	60W	WHEEL