

SAM 022816**UNIMAG Tipo PFA-20****Gruppo**

Lubrificazione

Produttori

UNIMAG

Tipo

PFA-20



Contenuto massima
 Capacità
 Larghezza del filtro in carta
 Lunghezza filtro di carta
 Motore pompa
 Dimensioni:

Lunghezza
 Larghezza
 Altezza

100 l
 20 l/min
 500 mm
 90 m
 25 W

1050 mm
 720 mm
 660 mm



PFA-120

PFA PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.



Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:

1. Surface Grinding Machine
2. Centerless Grinding Machine
3. Internal/External Grinding Machine
4. Honing Machine
5. Broad Grinding Machine
6. Gear Grinding Machine
7. Polisher

DIMENSION DIAGRAM



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL L	L	A	B	C	H	PUMP (H-P) INLET	OUTLET	MOTOR	FILTER PAPER	Notes
PFA-20	20	100	1050	800	400	400	720	600	1/8"	PF1/2"	25W	
PFA-40	40	120	1300	1000	600	400	720	600	1/8"	PF1/2"	25W	W/ 1500MM
PFA-60	60	140	1350	1100	600	400	720	600	1/8"	PF1/2"	25W	L/ 90M
PFA-80	80	160	1400	1100	600	400	720	600	1/4"	PF3/4"	25W	
PFA-120	120	210	1500	1300	800	400	920	740	1/2"	PF3/4"	40W	W/ 1500MM
PFA-160	160	260	1800	1600	800	400	920	740	1/2"	PF3/4"	40W	L/ 90M
PFA-240	240	440	1550	1700	1000	400	1300	740	1"	PF1"	60W	
PFA-300	300	540	2150	1900	1000	400	1300	740	1"	PF1"	60W	W/ 1000MM
PFA-500	500	980	3240	2900	1000	400	1300	740	1 1/2"	PF1 1/2"	60W	L/ 90M WHEEL