

SAM 022821

UNIMAG Tipo PFA-40

Gruppo Lubrificazione
Produttori UNIMAG
Tipo PFA-40



Contenuto massima
Capacità
Larghezza del filtro in carta
Lunghezza filtro di carta
Motore pompa
Dimensioni:
Lunghezza
Larghezza
Altezza

120 l
40 l/min
500 mm
90 m
25 W

1200 mm
720 mm
660 mm



PFA PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 30µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.

APPLICATION:

1. Surface Grinding Machine	5. Bore Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM

SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. l	L	A	B	C	H	PUMP (HP)	FILTER PAPER	WHEEL	
PFA-20	20	100	800	800	400	400	720	600	1/8	PP1/2"	25W
PFA-40	40	120	1300	1000	600	400	720	600	1/8	PP1/2"	25W
PFA-80	80	140	1350	1150	800	400	720	600	1/8	PP1/2"	25W
PFA-80	80	160	1360	1200	800	400	720	600	1/4	PP3/4"	25W
PFA-120	120	210	1300	1300	800	400	920	740	1/2	PP3/4"	40W
PFA-160	160	260	1800	1600	800	400	920	740	1/2	PP3/4"	40W
PFA-240	240	440	1550	1750	1060	430	1320	740	1	PP1"	60W
PFA-300	300	540	2150	1950	1060	430	1320	740	1	PP1"	60W
PFA-500	500	980	3240	2950	1060	430	1320	740	1 1/2	PP1 1/2"	60W