



Inventory number: 20228

Press brake  
AMADA ITS2 2  
PROMECAM



### Technical data

Pressure	25 to
Max. Bending length	1250 mm
Passage between press bars	320 mm
Distance between the	1020
Max. stroke	100 mm
Depth of throat	200 mm
Feed rate	75 mm/s
Working speed	10 mm/s
Return stroke speed	80 m/min
Table length	1200 mm
Table width	60 mm
Table height	865 mm
Number of spacers	6 pce
Height of the spacers	120 mm
Number of cylinder	1 pce
Oil capacity	30 l
Voltage 50 Hz 3x	400 Volt
Motor power	4 kW
Machine's weight about	1600 kg
Overall dimensions machine:	
Length	1800 mm
Width	1200 mm
Height	2000 mm









PLIAGE EN L'AIR  
AIR BENDING  
FREIES ABKANTEN  
PLEGADO EN AIRE

LISTA DEGRADIMOS AD  
E113 COLGATHEIM

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100

The control panel features the following components:

- Emergency Stop:** A large yellow button with a lightning bolt symbol.
- Start/Run:** A green button with a power symbol.
- Stop:** A button with a lightning bolt and a hand icon.
- Mode Selection:** Three rotary switches with diagrams showing different machine configurations.
- Directional Control:** A rotary switch with arrows indicating movement directions.
- Light Control:** A switch labeled "Licht".
- Additional Controls:** A large rotary switch with a lightning bolt and a hand icon, and a smaller rotary switch with a lightning bolt and a hand icon.



