



Inventory number: 20228

Press brake
AMADA ITS2 2
PROMECAM



Technical data

Pressure	25 to
Max. Bending length	1250 mm
Passage between press bars	320 mm
Distance between the	1020
Max. stroke	100 mm
Depth of throat	200 mm
Feed rate	75 mm/s
Working speed	10 mm/s
Return stroke speed	80 m/min
Table length	1200 mm
Table width	60 mm
Table height	865 mm
Number of spacers	6 pce
Height of the spacers	120 mm
Number of cylinder	1 pce
Oil capacity	30 l
Voltage 50 Hz 3x	400 Volt
Motor power	4 kW
Machine's weight about	1600 kg
Overall dimensions machine:	
Length	1800 mm
Width	1200 mm
Height	2000 mm









PLIAGE EN L'AIR
AIR BENDING
FREIES ABKANTEN
PLEGADO EN AIRE

LISTA DEGRADIMOS AD
E113 COLGATIEM
E-100000

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100

The control panel features the following components:

- Emergency Stop:** A large yellow button with a lightning bolt symbol.
- Start/Run:** A green button with a power symbol.
- Stop:** A button with a lightning bolt and a hand icon.
- Mode Selection:** Three rotary switches with diagrams showing different machine configurations.
- Directional Control:** A rotary switch with arrows indicating movement directions.
- Light Control:** A switch labeled "Licht".
- Power Off:** A button with a power symbol and a lightning bolt.
- Diagrammatic Controls:** Several rotary switches with diagrams of electrical components like capacitors and relays.





EN FONCTION DE LA LONGUEUR A PLIER CONSULTER LE MANOMETRE
FOLLOWING THE BENDING LENGTH READ THE MANOMETER
GEMÄSS DER ABKANTLÄNGE DAS MANOMETER ABLESEN

**LIMITER LA FORCE
LIMIT THE TONNAGE
DEN DRUCK BEGRENZEN**