



Inventory number: 21633

Cylindrical grinder  
KELLENBERGER 600 U



### Technical data

Centre height	125 (175) mm
Distance between centres	600 mm
Max. Longitudinal travel	900 mm
Max. transversal travel	245 mm
Grinding wheel:	
Diameter	400 mm
Width	50 mm
Bore	127 mm
Grinding wheel speeds:	
number (steps)	3
from	1500 rpm
up to	2200 rpm
Angular displacement	270 °
Work piece spindle head:	
speeds:	
stepless	
from	20 rpm
up to	400 rpm
rotatable	360 °
Spindle taper	5 MT
Taper in tailstock:	3 MT
Table angular displacement	10 °
Table speed:	
stepless	
from	0.02 m/min
up to	6 m/min

Voltage	50 Hz 3x	380 Volt
External Grinding wheel motor		4 HP
Total power required		6 kW
Machine's weight about		2200 kg
Overall dimensions machine:		
Length		3000 mm
Width		1750 mm
Height		1600 mm
Various accessories:		
Internal grinding attachment		
Spindle speeds		14000 rpm
Flange for outer pane		1 pce
Two-jaw steady rest		
Collet-chuck attachment		W20
Grinding wheel guard		
Safety device		
Sliding door		
Set of elevation plates		50 mm

























