



Inventory number: 21942

Jig boring machine
HAUSER 3 BA



Technical data

| | |
|-------------------------------------|--------|
| Table length | 550 mm |
| Table width | 320 mm |
| Number of T-channels | 6 |
| T-channel width | 10 mm |
| Distance of the T-slots | 40 mm |
| Table load max. | 400 kg |
| Longitudinal travel (X-axis) | 400 mm |
| Transversal travel (y-axis) | 250 mm |
| Vertical travel (z axis) | 400 mm |
| Drill capacity in steel | 20 mm |
| Taper in spindle: MT | 2 |
| Stroke of drilling spindle (Z-axis) | 130 mm |
| Bore diameter max. | 75 mm |
| Distance table to spindle | 590 mm |

| | |
|-----------------------------|-----------|
| Spindle speeds: | |
| stepless | |
| from | 60 rpm |
| up to | 3000 rpm |
| Feeds: | |
| Drill spindle slide: | |
| number (steps) | 2 |
| from | 0.03 mm/r |
| up to | 0.06 mm/r |
| Voltage 50 Hz 3x | 380 Volt |
| Spindle motor | 0.80 HP |
| Machine's weight about | 1100 kg |
| Overall dimensions machine: | |
| Length | 1200 mm |
| Width | 1150 mm |
| Height | 1750 mm |
| Various accessories: | |
| Rotary table diameter | 300 mm |
| Drill chuck | |
| Set of drill chucks | |
| Centering microscop | |
| Lamp | |
| 3-jaw chuck diameter | mm |



















