



Inventory number: 22228

Cylindrical grinder  
KELLENBERGER 600 UR



### Technical data

|                               |           |
|-------------------------------|-----------|
| Centre height                 | 125 mm    |
| Distance between centres      | 600 mm    |
| Grinding wheel:               |           |
| Diameter                      | 350 mm    |
| Width                         | 50 mm     |
| Bore                          | 127.0 mm  |
| Grinding wheel speeds:        |           |
| number (steps)                | 4         |
| from                          | 1500 rpm  |
| up to                         | 3600 rpm  |
| Angular displacement          | 270 °     |
| Work piece spindle head:      |           |
| speeds:                       |           |
| stepless                      |           |
| from                          | 20 rpm    |
| up to                         | 400 rpm   |
| rotatable                     | 360 °     |
| Spindle taper                 | 5 MT      |
| Taper in tailstock:           | 3 MT      |
| Table angular displacement    | 10 °      |
| Table speed:                  |           |
| stepless                      |           |
| up to                         | 6.0 m/min |
| Voltage 50 Hz 3x              | 380 Volt  |
| External Grinding wheel motor | 4.0 HP    |
| Machine's weight about        | 2200 kg   |

Overall dimensions machine:

|        |         |
|--------|---------|
| Length | 3000 mm |
| Width  | 1750 mm |
| Height | 1600 mm |

Various accessories:

Tailstock with fine adjustment

Coolant system

Grinding wheel with flange

Safety device









