



Inventory number: 22309

CNC jig grinder
HAUSER S 35-400
GE FANUC Series O-M



Technical data

1 column execution

Table:

Table length	600 mm
Table width	380 mm
T-channel width	10 mm
Number of spline	6
Distance of the T-slots	50 mm
Table load max.	200 kg

Carriage:

Longitudinal travel (X-axis)	500 mm
Transversal travel (y-axis)	300 mm

Travel of the vertical slide 450 mm

Passage from grinding motor to table 485 mm

Max. grinding diameter 230 mm
with display-plate 360 mm

Stroke of spindle-nose 340 mm

Max. angle with taper grinding:

up to 16 °

Vertical travel of grinding spindle:

stepless from 1 mm

up to 110 mm

Travel speeds:

stepless

from 0.5 m/min

up to 12 m/min

Planetary motion speeds: c axis

stepless

from 5 rpm

up to 250 rpm

Feeds:

X axis 0 - 12 m/min

Y axis 0 - 12 m/min

W axis 900 mm/min

Voltage 50 Hz 3x 380 Volt

Spindle motor 7.5 kW

Machine's weight about 4000 kg

Overall dimensions machine:

Length 2700 mm

Width 1700 mm

Height 2850 mm










CO₂-Löschanlage
CO₂- Fire Extinguishing Installation
Installation d'extinction à CO₂
Bei Feuergefahr oder Ausströmen des Kohlendioxids:
Raum sofort verlassen! Gesundheitsgefahr!
In case of fire alarm or carbon dioxide outgassing:
Immediately leave the room! Danger to health!
En cas d'alarme incendie ou dégagement de gaz carbonique:
Quitter immédiatement le local! Danger pour la santé!
HAUSER 1234 443333 Inverkehr gebracht - 9-2002 Gds. 02 - Germany

HAUSER S3

HAUSER READY 

   

30
25
20
15
10
5
0

  

  

REF 

M4  1
M3  2
M2  3
M1  4









