



Inventory number: 22408

CNC Turning-Milling-Drilling Center
DMG MORI NZX 1500/800SY
FANUC 31iB
2016



Technical data

Number of turning spindles	2
Number of revolvers	2
Swing diameter over bed	800 mm
Max. turning diameter	320 mm
Max. bar diameter	52 mm
Turret carriage:	
Carriage 1:	
Travels:	
Longitudinal travel (Z-axis)	810 mm
Longitudinal travel (X-axis)	210 mm
Transversal travel (y-axis)	110 mm
Carriage 2:	
Longitudinal travel (Z-axis)	810 mm
Transversal stroke (X axis)	210 mm
Transversal travel (y-axis)	110 mm
Turret slide:	
Number of positions	16 (2x)
Driven tools turret	16
Spindle speeds	6000 rpm
Tool shank cross section	20 mm
Power of driven tools	7.5 / 5.5 kW
Main spindle:	
Spindle nose	JIS A2-5
Spindle hole	61 mm
Spindle speeds:	
stepless	

from	0 rpm
up to	6000 rpm
Spindle power	22 / 18.5 kW
Back spindle:	
Spindle nose	JIS A2-5
Spindle hole	61 mm
max. speed	6000 rpm
Rapid traverse X	30 m/min
Rapid traverse Z	50 m/min
Rapid traverse Y	20 m/min
Spindle motor	22 / 18.5 kW
Machine's weight about	8100 kg
Overall dimensions machine:	
Length	4396 mm
Width	2835 mm
Height	2320 mm
Various accessories:	
Direct measuring system X axis	
Lamp	
Coolant system	
Coolant through the counter spindle	
Loader interface	
Parts catcher	
Workpiece conveyor	
Chip conveyor	















