



Inventory number: 22583

Universal milling machine
SIXIS S 103 R



Technical data

| | |
|---|------------|
| Table length | 600 mm |
| Table width | 210 mm |
| Number of T-channels | 5 |
| T-channel width | 12H7 mm |
| Distance of the T-slots | 40 mm |
| Longitudinal travel (X-axis) | 300 mm |
| Transversal travel (y axis) | 175 mm |
| Vertical travel (z axis) | 400 mm |
| Distance from vertical spindle to table | 320 mm |
| Spindle speeds: | |
| number (steps) | 9 |
| from | 60 rpm |
| up to | 1200 rpm |
| Taper in spindle | 30 ISO |
| Feeds steps: | 8 |
| longitudinal from | 12 mm/min |
| up to | 216 mm/min |

| | |
|------------------------------|------------|
| vertical from | 6 mm/min |
| up to | 108 mm/min |
| Rapid traverse: | |
| longitudinal | 1 m/min |
| vertical | 0.5 m/min |
| Voltage 50 Hz 3x | 380 Volt |
| Motor output | 1.5 HP |
| Total power required | 2 HP |
| Machine's weight about | 880 kg |
| Overall dimensions machine: | |
| Length | 1100 mm |
| Width | 1100 mm |
| Height | 1600 mm |
| Various accessories: | |
| Set of toolholders | |
| Swivelling protection device | |









